



# Shielded D-Sub Backshells DMVZK Series

## TECHNICAL SPECIFICATIONS

Material:	Zinc, Ni-plated
Temp. range:	-40°C - 120°C
Cable strain relief:	Cable clamp with 2 assembly screws
Cable diameter:	4.0 - 13.0 mm
Locking screws:	Delivered with pre-mounted UNC4-40 jackscrews. M2.5, M2.6 and M3.0 as option
Cable outlet:	Angled
Attenuation factor:	> 60 dB between 300 MHz and 900 MHz



TYPE	A	B
DMVZK9	32	39,5
DMVZK15	40,3	39,5

## PART NUMBERING SYSTEM

DMVZK9 - - K

Series: \_\_\_\_\_  
DMVZK  
Size: \_\_\_\_\_  
9 & 15

Packaging:  
K = Kit package  
BULK = Bulk package / 100 pcs  
Thread (jackscrew):  
Omit = UNC4-40  
M2.5  
M2.6  
M3.0

## FEATURES

- Available in sizes 9- and 15-way
- Minimise interference from electromagnetic and RF sources
- Pre-mounted jackscrew provide easy assembly
- Non-static parts avoid ESD problems
- Accept round foil and braided cable types
- Approved according VDE 0871, FCC 20780 and 89/336/EU
- Company logotype available upon request
- Jackscrews with UNC 4-40 thread as standard, M2.5, M2.6 or M3.0 as option
- For custom designed solutions, please consult factory